

Linear Light



Diffusive linear profile for wall or ceiling mounted indoor installation ideal for the illumination of common spaces, circulation areas, shops shop-windows, museums, large areas, corridors, entrances, living rooms kitchens, bedrooms.



General Data

Item No.	APL140I / APL142I
Power	30 / 60 W
LED Type	2835 SMD LED CHIP
Luminous flux	110 lm/w
CCT	2700 ~ 6000K
CRI	80+
Beam angle	Asymmetric LR25°/Double Asymmetric 50°/Flat 90°
Dimension (mm)	600/1200 x64x40
Cut out (mm)	42x42 /42*115 /80*80 /42*195 /117*117 /42*383
Life Time:	50,000 Hrs
Adjustable	No
Working Temp	-20°~ +50°
Surge protection	Yes

Construction Data

IP rating	IP20
Finishing	<input type="radio"/> White <input checked="" type="radio"/> Black <input type="radio"/> Aluminum
Housing	Aluminum
Diffuser	Lens

Accessories

Suspension / Ceiling Surface / Rail mounting

OPTIONS

Dimmable	YES
Emergency	YES

Electrical Data

Input voltage	AC100~277V
Insulation Class	I
Cable	Open wires
Driver	Integrated high voltage driver

Optics

