



Diffusive linear profile for wall or ceiling mounted indoor installation ideal for the illumination of common spaces, circulation areas, shops shop-windows, museums, large areas, corridors, entrances, living rooms kitchens, bedrooms.



General Data

| | |
|------------------|-------------------------------|
| Item No. | APL146I / APL148I |
| Power | 40 / 60 W |
| LED Type | SMD LED BOARD CHIPS |
| Luminous flux | 100 lm/w |
| CCT | 2700 ~ 6000K |
| CRI | 80+ |
| Beam angle | 120° |
| Dimension (mm) | 1200x50x70 / 1800x50x70 (WxH) |
| Cut out (mm) | / |
| Life Time: | 50,000 Hrs |
| Adjustable | No |
| Working Temp | -20° ~ +50° |
| Surge protection | Yes |

Construction Data

| | |
|-----------|---|
| IP rating | IP40 |
| Finishing | <input type="radio"/> White <input checked="" type="radio"/> Black <input type="radio"/> Aluminum |
| Housing | Aluminum |
| Diffuser | Opal Polycarbonate |

Accessories

⚙️ Suspension kit

OPTIONS

| | |
|-----------|-----|
| Dimmable | YES |
| Emergency | YES |

Electrical Data

| | |
|------------------|--------------------------------|
| Input voltage | AC100~255V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | Integrated high voltage driver |

Optics



α 120°