



Spot ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



| General Data | |
|------------------|--------------------------------|
| Item No. | DLRC138I / DLRC140I / DLRC142I |
| Power | 15 / 20 / 30 W |
| LED Type | CREE / Luminus COB LED |
| Luminous flux | 120 lm/w |
| CCT | 2700 ~ 6000K |
| CRI | 80+ |
| Beam angle | 60° |
| Dimension (mm) | Ø132x69 / Ø190x69 / Ø264x69 |
| Cut out (mm) | Ø120 / Ø170 / Ø252 |
| Life Time: | 50,000 Hrs |
| Adjustable | No |
| Working Temp | -20° ~ +50° |
| Surge protection | Yes |

| Construction Data | |
|-------------------|--|
| IP rating | IP40 |
| Finishing | <input type="radio"/> White <input checked="" type="radio"/> Black |
| Housing | Aluminum |
| Diffuser | PC |

| Accessories | |
|-------------|--|
| / | |

| OPTIONS | |
|-----------|-----|
| Dimmable | YES |
| Emergency | YES |

| Electrical Data | |
|------------------|------------------------------|
| Input Voltage | AC100~245V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | External high voltage driver |