



Downlight indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



General Data	
Item No.	DLRC144I / DLRC146I / DLRC148I / DLRC150I DLRC152I
Power	12 / 18 / 24 / 30 W
LED Type	CREE / Luminus COB LED
Luminous flux	120 lm/w
CCT	2700 ~ 6000K
CRI	80+
Beam angle	24° / 36° / 60°
Dimension (mm)	Ø110x72/Ø140x82/Ø160x92/Ø210x112
Cut out (mm)	Ø90/Ø120/Ø160/Ø190
Life Time:	50,000 Hrs
Adjustable	No
Working Temp	-20° ~ +50°
Surge protection	Yes

Construction Data	
IP rating	IP40
Finishing	<input type="radio"/> White <input checked="" type="radio"/> Black
Housing	Aluminum
Diffuser	PC

Accessories	
/	

OPTIONS	
Dimmable	YES
Emergency	YES

Electrical Data	
Input Voltage	AC100~245V
Insulation Class	I
Cable	Open wires
Driver	External high voltage driver

Optics	
	$\alpha$ 18°
	$\alpha$ 24°
	$\alpha$ 36°