



Downlight ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



General Data	
Item No.	DLRC180I
Power	5 / 7 / 9 / 12 / 15 / 20 / 30 W
LED Type	EPISTAR SMD COB LED
Luminous flux	100 lm/w
CCT	2700 ~ 6000K
CRI	80+
MacAdam's step	3
Beam angle	60°
Dimension (mm)	Ø80x40/Ø96x47/Ø113x55/Ø138x64/Ø165x74 Ø195x85/Ø228x97
Cut out (mm)	Ø75 / Ø85 / Ø100 / Ø120 / Ø140 / Ø170 / Ø200
Life Time	50,000 Hrs
Adjustable	Yes
Working Temp	-20° ~ +50°
Surge protection	Yes

Construction Data	
IP rating	IP44
Finishing	 White  Black
Housing	Aluminum
Diffuser	PC
Reflector	Chrome
UGR	<19
Accessories	
/	

OPTIONS	
Dimmable	YES
Emergency	YES

Electrical Data	
Input Voltage	AC100~245V
Insulation Class	I
Cable	Open wires
Driver	External high voltage driver