




Adjustable Flood light for ground, wall or ceiling mounted outdoor replacement for 1500-2000W MHL/HPS/HID/CFL light installation, ideal for the illumination of architectural facades and outdoor large areas.



| General Data | |
|------------------|-----------------------------|
| Item No. | FDL1200 |
| Power | 600 W |
| LED Type | Lumileds |
| Luminous flux | 160 lm/w |
| CCT | 2700 ~ 6500K |
| CRI | 80+ |
| Beam angle | 10° / 20° / 40° / 60° / P50 |
| Dimension (mm) | 565x382x155 |
| Cut out (mm) | / |
| Life Time: | 50,000 Hrs |
| Adjustable | Yes |
| Working Temp | -20° ~ +50° |
| Surge protection | Yes |

| Construction Data | |
|-------------------|---|
| IP rating | IP66 |
| Finishing |  Silver |
| Housing | Die-Case Aluminum |
| Diffuser | PC |

| Accessories | |
|------------------------------------|--|
| Bracket / Photocell / Shorting cap | |

| OPTIONS | |
|-----------|-----|
| Emergency | YES |

| Electrical Data | |
|------------------|--------------------------------|
| Input voltage | AC100~245V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | Integrated high voltage driver |