



Spetraluce Linear LED highbay are low profile, light weight and designed for long life with low maintenance and great performance. These LED luminaires are designed to quickly and easily upgrade existing HID and fluorescent fixtures.

General Data	
Item No.	HBL286O
Power	50 / 100 / 150 / 200 / 250 / 300 / 400 / 500 W
LED Type	Lumileds LED CHIPS 3030
Luminous flux	130 lm/w
CCT	2700 ~ 6500K
CRI	80+
Beam angle	30°/60°/ 90°/60x 120°
Dimension LxWxH (mm)	353x115x144/620x115x144/887x115x144 1154x115x144/1421x115x144/947x230x173 1214x230x173/1481x230x173
Cut out (mm)	/
Life Time:	50,000 Hrs
Adjustable	Yes
Working Temp	-20° ~ +50°
Surge protection	Yes

Construction Data	
IP rating	IP66
Finishing	<input checked="" type="radio"/> Grey <input type="radio"/> White
Housing	Aluminum die cast
Diffuser	Clear polycarbonate lens
Weight	19 kg

Accessories (Optional)	
Bracket / Microwave sensor / Daylight sensor	

OPTIONS	
Dimmable	YES
Emergency	YES

Electrical Data	
Input voltage	AC100~277V
Insulation Class	I
Cable	Open wires
Driver	Meanwell Integrated Meanwell high voltage driver

