



















Trimless Spot ceiling outdoor installation, ideal for the illumination of common spaces, circulation, outdoor applications

| General Data | | |
|------------------|-------------------------|--|
| Item No. | SLRC139O | |
| Power | 12 W | |
| LED Type | CREE LED Chip | |
| Luminous flux | 120 lm/w | |
| CCT | 2700K,3000K,4000K,6000K | |
| CRI | 80+ | |
| Beam angle | 12° / 24° / 36° / 50° | |
| Dimension (mm) | Ф86*Н85 | |
| Cut out (mm) | Ø75 | |
| Life Time: | 50,000 Hrs | |
| Adjustable | Yes | |
| Working Temp | -20° ~ +50° | |
| Surge protection | Yes | |

| Construction Data | |
|-------------------|-------------|
| IP rating | IP54 |
| Finishing | White Black |
| Housing | Aluminum |
| Diffuser | LENS |

| Accessories | | |
|-------------|--|--|
| / | | |

| OPTIONS | | |
|-----------|-----|--|
| Dimmable | YES | |
| Emergency | YES | |

| Electrical Data | |
|------------------|------------------------------|
| Input Voltage | AC100~255V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | External high voltage driver |