



Spot ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



| General Data     |                                                                  |
|------------------|------------------------------------------------------------------|
| Item No.         | SLRC358I / SLRC360I / SLRC362I / SLRC364I<br>SLRC366I / SLRC368I |
| Power            | 5 / 10 / 15 / 20 / 30 / 35 W                                     |
| LED Type         | CREE / Luminus COB LED                                           |
| Luminous flux    | 120 lm/w                                                         |
| CCT              | 2700 ~ 6000K                                                     |
| CRI              | 80+                                                              |
| Beam angle       | 10° / 15° / 24° / 38°                                            |
| Dimension (mm)   | Ø62x85/Ø86x115/Ø110x140/Ø140x155<br>Ø160x200/Ø180x210            |
| Cut out (mm)     | Ø55/Ø75/Ø85/Ø125/Ø145/Ø165                                       |
| Life Time:       | 50,000 Hrs                                                       |
| Adjustable       | Yes                                                              |
| Working Temp     | -20° ~ +50°                                                      |
| Surge protection | Yes                                                              |

| Construction Data |              |
|-------------------|--------------|
| IP rating         | IP20         |
| Finishing         | White  Black |
| Housing           | Aluminum     |
| Diffuser          | PC           |

| Accessories |  |
|-------------|--|
| /           |  |

| OPTIONS   |     |
|-----------|-----|
| Dimmable  | YES |
| Emergency | YES |

| Electrical Data  |                              |
|------------------|------------------------------|
| Input Voltage    | AC100~245V                   |
| Insulation Class | I                            |
| Cable            | Open wires                   |
| Driver           | External high voltage driver |

| Optics |       |
|--------|-------|
|        |       |
| α 18°  | α 24° |
|        |       |
| α 36°  |       |

