



Spot ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



General Data

| | |
|------------------|--------------|
| Item No. | SLRC486I |
| Power | 12 W |
| LED Type | CREE COB LED |
| Luminous flux | 120 lm/w |
| CCT | 2700 ~ 6000K |
| CRI | 80+ |
| Beam angle | 24° / 35° |
| Dimension (mm) | Ø85x80 |
| Cut out (mm) | Ø75 |
| Life Time: | 50,000 Hrs |
| Adjustable | Yes |
| Working Temp | -20° ~ +50° |
| Surge protection | Yes |

Construction Data

| | |
|-----------|--|
| IP rating | IP40 |
| Finishing | <input type="radio"/> White <input checked="" type="radio"/> Black |
| Housing | Aluminum |
| Diffuser | PC |

Accessories

/

OPTIONS

| | |
|-----------|-----|
| Dimmable | YES |
| Emergency | YES |

Electrical Data

| | |
|------------------|------------------------------|
| Input Voltage | AC100~245V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | External high voltage driver |