



Spot ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.



General Data	
Item No.	SLRC498I / SLRC500I / SLRC502I / SLRC504I
Power	6 / 12 / 18 / 24 W
LED Type	CREE / Luminus COB LED
Luminous flux	120 lm/w
CCT	2700 ~ 6000K
CRI	80+
Beam angle	15° / 24° / 36°
Dimension (mm)	Ø80x81/Ø140x80x81/Ø234x68x81/Ø140x140x81
Cut out (mm)	Ø70/Ø130x60/Ø188x68/Ø130x130
Life Time:	50,000 Hrs
Adjustable	Yes
Working Temp	-20° ~ +50°
Surge protection	Yes

Construction Data	
IP rating	IP40
Finishing	<input type="radio"/> White <input checked="" type="radio"/> Black
Housing	Aluminum
Diffuser	PC

Accessories	
/	

OPTIONS	
Dimmable	YES
Emergency	YES

Electrical Data	
Input Voltage	AC100~245V
Insulation Class	I
Cable	Open wires
Driver	External high voltage driver

Optics	
α 18°	α 24°
	α 36°

