



Diffusive linear profile for wall or ceiling mounted indoor installation ideal for the illumination of common spaces, circulation areas, shops shop-windows, museums, large areas, corridors, entrances, living rooms kitchens, bedrooms.

General Data

Item No.	SLRC502I / SLRC504I / SLRC506I / SLRC508I SLRC510I / SLRC512I
Power	3 / 9 / 12 / 15 / 27/ 30 W
LED Type	CREE / Luminus COB LED
Luminous flux	120 lm/w
CCT	2700 ~ 6000K
CRI	80+
Beam angle	60°
Dimension (mm)	52x52x56 / 52x125x56 / 90x90x56 / 52x205x56 127x127x56 / 52x393x56
Cut out (mm)	42*42 / 42*115 / 80*80 / 42*195 / 117*117 / 42*383
Life Time:	50,000 Hrs
Adjustable	No
Working Temp	-20° to +50°
Surge protection	Yes

Construction Data

IP rating	IP20
Finishing	☐ White ☒ Black ☐ Aluminum
Housing	Aluminum
Diffuser	Lens

Accessories

/

OPTIONS

Dimmable	YES
Emergency	YES

Electrical Data

Input voltage	AC100~255V
Insulation Class	I
Cable	Open wires
Driver	Integrated high voltage driver