

Linear Spot



Spot ceiling indoor installation, ideal for the illumination of common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.

General Data	
Item No.	SLRC502I / SLRC504I / SLRC506I / SLRC508I SLRC510I / SLRC512I
Power	3 / 9 / 12 / 15 / 27/ 30 W
LED Type	CREE / Luminus COB LED
Luminous flux	120 lm/w
CCT	2700 ~ 6000K
CRI	80+
Beam angle	60°
Dimension (mm)	52x52x56 / 52x125x56 / 90x90x56 / 52x205x56 127x127x56 / 52x393x56
Cut out (mm)	42*42 /42*115 /80*80 /42*195 /117*117 /42*383
Life Time:	50,000 Hrs
Adjustable	No
Working Temp	-20° ~ +50°
Surge protection	Yes

Construction Data	
IP rating	IP20
Finishing	☐ White ☒ Black
Housing	Aluminum
Diffuser	PC

Accessories	
/	

OPTIONS	
Dimmable	YES
Emergency	YES

Electrical Data	
Input voltage	AC100~245V
Insulation Class	I
Cable	Open wires
Driver	External high voltage driver