



















Spot ceiling indoor installation, ideal for the illumination of $% \left\{ 1\right\} =\left\{ 1\right\} =\left\{$ common spaces, circulation, areas, shops, shop-windows museums, large areas corridors, entrances, living rooms, kitchens, bedrooms, closets.

| General Data | |
|------------------|------------------------------------|
| Item No. | SLRC694I |
| Power | 5 / 7 / 12 / 20 W |
| LED Type | OSRAM LED CHIP |
| Luminous flux | 110 lm/w |
| CCT | 2700 ~ 6000K |
| CRI | 80+ |
| Beam angle | 60° |
| Dimension (mm) | Ø60x40 / Ø80x45 / Ø90x48 / Ø100x53 |
| Cut out (mm) | Ø55 / Ø85 / Ø95 |
| Life Time | 50,000 Hrs |
| Adjustable | Yes |
| Working Temp | -20° ~ +50° |
| Surge protection | Yes |

| Construction Data | |
|-------------------|------------------------------|
| IP rating | IP40/IP44 |
| Finishing | White |
| Housing | Aluminum |
| Diffuser | PC |
| Reflector | White / Black |
| | |
| Accessories | |
| / | |
| | |
| | |
| OPTIONS | |
| Dimmable | YES |
| Emergency | YES |
| | |
| | |
| Electrical Data | |
| Input Voltage | AC100~245V |
| Insulation Class | I |
| Cable | Open wires |
| Driver | External high voltage driver |
| | |

