





Wall light



Light Distribution Curve (3000K, 30°)



Lux distance Curve (3000K, 30°)



Height Center E Beam Angle:32.8 Average E Diameter

Illumination Picture (30°)



Parameter

General Data	
Item No.	WLR2400
Power	3 Watts
LED type	1 PC CREE XPE LED (VVV, NWV, CWV.1 Watt to 3 Watt optional)
Luminous flux	110~130lm
CCT	2700K, 3000K, 4000K, 6000K
CRI	80+
Beam angle	30°
Dimension	70 x 34.5 (mm) Diameter x Height
Cut out	62 mm
Working Temp	-20 ~ +50
Life Time	50,000 Hrs
Certifications	CE, RoHS
Electrical Data	
Input voltage	DC12V/DC24V (AC100~265V optional)
Insulation class	Class III
Cable	1 x cable 0.3 M H05RN-F 2x0.5mm square to open wires
Driver	Low voltage constant current output, excluding the transformer. (With separately driver for options)
Construction Data	
IP rating	IP65 Waterproof
IK rating	IK06
Housing	Polished chrome Aluminium
Protection finishing	Polished chrome
Trim	Polished chrome Aluminium
Glass	Tempered glass
Loading capacity	320 kgs
Cable Gland	IP65 Aluminium part
Gasket	O-ring PMQ silicone seal
Accessories	
Mounting Sleeve	Anti-corrosion PVC. Grey.